

SOLENOID VALVES . . .

The coil chart shows applicable voltages for various frequencies. Specify voltages and frequencies as listed below when ordering. Consult factory for voltages and frequencies not listed.

SERIES 20, 80 COIL CHART

A.C. VOLTAGES		D.C. VOLTAGES	NON-MOLDED COIL NO.	MOLDED COIL NO.
60 HZ.	50 HZ.			
6	5	1.8	2C-102-A24	2C-2-K24
7	6	2.2	2C-103-A24	2C-3-K24
12	10	3.7	2C-104-A24	2C-4-K24
14	12	4.4	2C-105-A24	2C-5-K24
19	17	6	2C-106-A24	2C-6-K24
24	21	7.5	2C-107-A24	2C-7-K24
28	24	9	2C-108-A24	2C-8-K24
30	26	9.5	2C-109-A24	2C-9-K24
38	33	12	2C-110-A24	2C-10-K24
48	42	15	2C-111-A24	2C-11-K24
55	48	18	2C-112-A24	2C-12-K24
77	67	24	2C-113-A24	2C-13-K24
120	100	38	2C-114-A24	2C-14-K24
138	120	45	2C-115-A24	2C-15-K24
157	135	48	2C-116-A24	2C-16-K24
240	208	75	2C-117-A24	2C-17-K24
360	314	115	2C-118-A24	2C-18-K24
380	330	120	2C-119-A24	2C-19-K24
480	415	150	2C-120-A24	2C-20-K24
575	500	187	2C-121-A24	2C-21-K24
730	635	240	2C-122-A24	2C-22-K24
825	720	265	2C-123-A24	
400	345	125	2C-125-A24	2C-25-K24
204	175	60	2C-126-A24	2C-26-K24
265	230	80	2C-127-A24	2C-27-K24
110	95	35	2C-130-A24	2C-30-K24
650	560	220	2C-131-A24	2C-31-K24
175	155	55	2C-132-A24	2C-32-K24
85	75	28	2C-133-A24	2C-33-K24
145	127	45	2C-134-A24	2C-34-K24
600	517	188		2C-35-K24
16	14	4.8	2C-136-A24	
320	275	100		2C-37-K24
120/240	(dual voltage coils)		2C-138-A24	(Non-molded only)
240/480	(dual voltage coils)		2C-139-A24	(Non-molded only)
120	110	42	2C-140-A24	2C-40-K24
24	24	7	2C-141-A24	2C-41-K24
240	220	77	2C-143-A24	2C-43-K24
220	188	65	2C-144-A24	2C-44-K24
230	200	67	2C-145-A24	2C-45-K24
67	60	20	2C-146-A24	2C-46-K24
EXPORT COILS				
126	110	42	2CE-114-A24	2CE-14-K24
135	115	44	2CE-115-A24	2CE-15-K24
255	220	78	2CE-116-A24	2CE-16-K24
275	240	90	2CE-117-A24	2CE-17-K24
435	380	145	2CE-119-A24	2CE-19-K24
500	440	172	2CE-120-A24	2CE-20-K24
100	85	32	2CE-140-A24	2CE-29-K24
DIODE RECTIFIED COILS				
240			2CD-117-A24	
120			2CD-128-A24	
24			2CD-131-A24	
115/400			2CD-132-A24	
120	110		20-17067	
		24	20-17073	