

# Metal Orifice Air Flow – SLPM

Orifice Diameter Inches	0.004	0.005	0.006	0.007	0.008	0.009	0.010	0.011	0.012	0.013	0.014	0.015	0.016	0.017	0.018	0.019	0.020	0.021	0.022	0.023	0.024	0.025	0.026	0.027	0.028	0.029	0.031	0.032	0.033		
Size Number	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	31	32	33		
Cv	0.00035	0.00061	0.00086	0.0012	0.0015	0.0019	0.0025	0.0028	0.0034	0.0038	0.0043	0.0050	0.0055	0.0067	0.0073	0.0080	0.0088	0.0096	0.011	0.012	0.013	0.014	0.016	0.017	0.018	0.019	0.022	0.024	0.025		
Supply Pressure – psig	1	0.035	0.064	0.086	0.127	0.170	0.226	0.280	0.308	0.398	0.45	0.52	0.61	0.66	0.77	0.86	0.96	1.05	1.13	1.29	1.41	1.54	1.67	1.91	1.95	2.21	2.39	2.65	2.88	3.03	
	5	0.09	0.16	0.21	0.30	0.40	0.52	0.65	0.71	0.92	1.06	1.21	1.41	1.54	1.76	1.98	2.22	2.47	2.65	2.97	3.24	3.53	3.83	4.34	4.44	4.94	5.31	5.86	6.42	6.80	
	10	0.12	0.22	0.31	0.43	0.57	0.74	0.93	1.01	1.29	1.48	1.68	1.95	2.01	2.26	2.54	2.83	3.16	3.53	4.33	4.75	5.18	5.55	6.15	6.43	7.18	7.83	8.63	9.40	9.98	
	15	0.16	0.28	0.39	0.54	0.72	0.93	1.17	1.26	1.62	1.85	2.10	2.44	2.50	2.85	3.23	3.57	4.01	4.41	5.35	5.93	6.43	6.95	7.58	7.95	8.78	9.58	10.6	11.6	12.3	
	20	0.19	0.33	0.46	0.65	0.85	1.10	1.38	1.49	1.92	2.19	2.49	2.87	2.97	3.40	3.86	4.26	4.84	5.22	6.35	6.95	7.58	8.15	8.90	9.28	10.3	11.2	12.4	13.5	14.3	
	25	0.22	0.39	0.53	0.75	0.98	1.27	1.59	1.71	2.20	2.50	2.86	3.28	3.42	3.92	4.45	4.91	5.59	6.01	7.30	7.95	8.65	9.38	10.2	10.7	11.7	12.8	14.2	15.4	16.3	
	30	0.25	0.44	0.60	0.85	1.12	1.43	1.80	1.93	2.47	2.82	3.21	3.69	3.87	4.43	5.03	5.56	6.33	6.81	8.23	8.98	9.75	10.6	11.5	12.0	13.2	14.4	15.9	17.3	18.4	
	40	0.30	0.54	0.74	1.05	1.38	1.77	2.21	2.37	3.04	3.45	3.93	4.51	4.78	5.47	6.21	6.85	7.81	8.42	10.1	11.0	12.0	13.0	14.1	14.7	16.1	17.5	19.4	21.1	22.5	
	50	0.36	0.65	0.88	1.26	1.65	2.10	2.62	2.80	3.58	4.07	4.64	5.31	5.70	6.51	7.40	8.15	9.26	10.0	11.9	13.0	14.2	15.4	16.6	17.3	19.0	20.7	22.9	25.0	26.6	
	60	0.42	0.75	1.02	1.46	1.91	2.42	3.02	3.23	4.13	4.70	5.34	6.13	6.61	7.56	8.58	9.46	10.7	11.6	13.8	15.0	16.4	17.7	19.2	20.0	21.9	23.8	26.4	28.8	30.7	
	70	0.48	0.86	1.16	1.67	2.17	2.75	3.43	3.66	4.68	5.32	6.05	6.96	7.53	8.61	9.77	10.8	12.2	13.2	15.6	17.0	18.5	20.1	21.7	22.7	24.8	27.0	30.0	32.7	34.9	
80	0.54	0.96	1.30	1.87	2.43	3.08	3.83	4.09	5.23	5.95	6.77	7.79	8.46	9.67	11.0	12.1	13.7	14.9	17.5	19.0	20.7	22.5	24.2	25.3	27.7	30.2	33.6	36.7	39.0		
90	0.60	1.07	1.44	2.08	2.69	3.40	4.23	4.51	5.78	6.58	7.49	8.62	9.38	10.7	12.2	13.4	15.2	16.5	19.3	21.0	22.9	24.9	26.8	28.0	30.7	33.5	37.2	40.6	43.2		
100	0.66	1.17	1.58	2.28	2.95	3.72	4.63	4.94	6.33	7.22	8.21	9.46	10.3	11.8	13.4	14.7	16.6	18.0	21.1	23.0	25.1	27.4	29.4	30.8	33.7	36.8	40.9	44.6	47.5		
Vacuum Level In. Hg.	Choked Flow	5	0.053	0.096	0.129	0.191	0.253	0.332	0.406	0.450	0.582	0.661	0.773	0.899	0.977	1.14	1.28	1.41	1.55	1.70	1.90	2.10	2.30	2.48	2.74	2.83	3.16	3.41	3.78	4.12	4.32
		10	0.069	0.124	0.168	0.246	0.324	0.421	0.519	0.564	0.730	0.834	0.972	1.12	1.24	1.41	1.58	1.79	1.96	2.18	2.44	2.68	2.89	3.13	3.44	3.58	4.00	4.30	4.77	5.16	5.43
		15	0.075	0.134	0.185	0.268	0.351	0.455	0.566	0.614	0.792	0.902	1.07	1.22	1.35	1.55	1.75	1.94	2.19	2.32	2.61	2.85	3.12	3.34	3.65	3.78	4.20	4.51	5.05	5.45	5.72
		20	0.075	0.134	0.185	0.268	0.351	0.455	0.566	0.614	0.792	0.902	1.07	1.22	1.35	1.55	1.75	1.94	2.19	2.32	2.61	2.85	3.12	3.34	3.65	3.78	4.20	4.51	5.05	5.45	5.72
30	0.075	0.134	0.185	0.268	0.351	0.455	0.566	0.614	0.792	0.902	1.07	1.22	1.35	1.55	1.75	1.94	2.19	2.32	2.61	2.85	3.12	3.34	3.65	3.78	4.20	4.51	5.05	5.45	5.72		

Orifice Diameter Inches	0.035	0.037	0.038	0.039	0.040	0.041	0.042	0.043	0.047	0.052	0.055	0.060	0.063	0.067	0.070	0.073	0.076	0.079	0.081	0.086	0.089	0.094	0.096	0.100	0.104	0.109	0.113	0.120	0.125		
Size Number	35	37	38	39	40	41	42	43	47	52	55	60	63	67	70	73	76	79	81	86	89	94	96	100	104	109	113	120	125		
Cv	0.028	0.031	0.032	0.033	0.036	0.038	0.039	0.041	0.048	0.059	0.068	0.081	0.088	0.10	0.11	0.12	0.13	0.14	0.15	0.17	0.18	0.20	0.21	0.23	0.25	0.27	0.31	0.34	0.37		
Supply Pressure – psig	1	3.48	3.83	4.13	4.46	4.60	4.67	4.99	5.36	6.43	8.04	9.40	11.2	12.2	14.2	15.9	16.9	18.5	20.3	21.7	23.5	25.4	28.4	30.1	32.9	35.5	39.6	43.1	47.8	50.1	
	5	7.67	8.48	9.09	9.70	10.2	10.6	11.3	12.1	14.2	17.6	20.3	23.9	26.1	30.3	33.8	36.1	39.4	43.1	46.0	51.1	54.9	61.9	65.0	70.8	76.6	84.8	92.1	102	108	
	10	10.6	11.8	12.5	13.6	14.4	14.8	15.6	16.8	19.4	24.5	27.1	32.2	35.2	40.7	45.6	48.5	52.9	57.3	61.6	67.9	72.3	81.0	85.5	92.3	102	112	118	135	148	
	15	13.1	14.5	15.4	16.7	17.7	18.2	19.1	20.4	23.6	29.7	32.9	39.0	42.6	49.3	55.3	58.8	64.0	69.4	74.5	82.1	87.3	97.8	103	111	123	135	143	163	178	
	20	15.3	17.0	18.1	19.6	20.9	21.4	22.5	24.0	27.7	35.0	38.7	45.9	50.1	58.0	65.0	69.0	75.3	81.4	87.3	95.6	102	114	121	130	144	158	167	190	210	
	25	17.7	19.6	20.8	22.6	24.0	24.7	25.9	27.6	31.9	40.3	44.6	52.8	57.7	66.7	74.7	79.3	86.4	93.5	100	110	117	131	138	149	164	180	191	219	241	
	30	20.0	22.2	23.6	25.6	27.2	28.0	29.4	31.3	36.0	45.6	50.4	59.7	65.2	75.4	84.3	89.5	97.4	105	113	125	132	148	156	168	185	204	216	248	273	
	40	24.8	27.4	31.7	31.6	33.6	34.6	36.3	38.7	44.5	56.3	62.2	73.6	80.3	92.7	104	110	120	129	139	153	162	181	191	207	228	251	267	306	337	
	50	29.5	32.6	34.8	37.6	40.1	41.3	43.3	46.0	52.9	66.9	74.0	87.4	95.4	110	123	131	142	153	164	181	192	215	227	247	272	299	317	364	401	
	60	34.3	38.0	40.6	43.8	46.7	48.1	50.3	53.5	61.5	77.7	85.8	101	110	127	142	151	164	177	189	210	223	250	264	286	315	347	368	422	465	
	70	39.2	43.3	46.3	50.0	53.3	55.0	57.4	61.0	70.0	88.4	97.6	115	126	145	162	171	186	202	216	240	254	285	301	327	360	396	421	482	531	
80	44.0	48.7	52.1	56.2	60.0	61.9	64.5	68.5	78.6	99.1	109	129	141	162	181	191	209	227	242	269	285	320	338	367	404	445	472	541	596		
90	50.0	54.2	57.8	62.4	66.7	68.9	71.5	76.0	87.2	109	121	143	156	179	200	211	231	251	268	298	316	354	374	406	447	492	522	598	660		
100	53.9	59.6	63.7	68.7	73.5	77.3	78.6	83.5	95.8	120	133	156	171	196	221	234	255	277	296	329	349	392	413	449	494	544	578	662	729		
Vacuum Level In. Hg.	Choked Flow	5	4.92	5.40	5.81	6.29	6.76	6.82	7.29	7.67	9.08	11.3	12.4	14.8	17.1	20.0	22.5	23.9	26.0	28.3	30.2	33.2	35.9	40.1	41.8	45.3	49.0	53.9	57.9	65.3	70.9
		10	6.18	6.78	7.29	7.85	8.31	8.50	9.08	9.58	11.1	13.9	15.4	18.2	21.2	24.4	27.2	29.9	32.5	35.3	37.7	41.5	44.8	50.0	52.1	56.6	61.2	67.2	72.2	81.4	88.4
		15	6.50	7.17	7.63	8.22	8.66	8.87	9.46	10.0	11.6	14.4	15.9	18.6	22.1	25.5	28.4	31.2	33.9	36.8	39.4	43.3	46.7	52.1	54.4	59.0	63.8	70.1	75.3	84.9	92.2
		20	6.50	7.17	7.63	8.22	8.66	8.87	9.46	10.0	11.6	14.4	15.9	18.6	22.1	25.5	28.4	31.2	33.9	36.8	39.4	43.3	46.7	52.1	54.4	59.0	63.8	70.1	75.3	84.9	92.2
30	6.50	7.17	7.63	8.22	8.66	8.87	9.46	10.0	11.6	14.4	15.9	18.6	22.1	25.5	28.4	31.2	33.9	36.8	39.4	43.3	46.7	52.1	54.4	59.0	63.8	70.1	75.3	84.9	92.2		

Standard Conditions 70°F, 14.7 psia

SCFH – Standard Cu. Ft. Per Hour

</